
Exercise Set 12: Solution
Quantum Computation

Exercise 1 *The Steane code*

- (a) The columns of the parity check matrix of the Hamming (7, 4) code are given by all binary non-zero vectors with $r = 3$ components (so that $2^r - 1 = 7$):

$$H_1 = \begin{pmatrix} 0 & 0 & 0 & 1 & 1 & 1 & 1 \\ 0 & 1 & 1 & 0 & 0 & 1 & 1 \\ 1 & 0 & 1 & 0 & 1 & 0 & 1 \end{pmatrix}$$

The generator matrix of $C_2 = C_1^\perp$ is given by vectors perpendicular to C_1 . Since a vector $c \in C_1$ satisfies $H_1 c^T = 0$, the rows of H_1 are 3 vectors \perp to C_1 . Note that C_1 has dimension 4, so $C_1^\perp = \{x \in \{0, 1\}^7 : x \cdot c = 0, \forall c \in C_1\}$ has dimension $7 - 4 = 3$ and $G_2 = H_1$ is therefore the generator matrix of C_2 .

Codewords of C_2 are given by

$$(u_1, u_2, u_3) \cdot G_2 = (u_3, u_2, u_2 \oplus u_3, u_1, u_1 \oplus u_3, u_1 \oplus u_2, u_1 \oplus u_2 \oplus u_3)$$

with $(u_1, u_2, u_3) \in \{0, 1\}^3$. The list of codewords of C_2 is therefore

$$0000000, 1010101, 0110011, 0001111, 0111100, 1011010, 1100110, 1101001 \quad (1)$$

To show that $C_2 \subset C_1$, it suffices to check that

$$H_1 \cdot (uG_2)^T = 0 \quad \forall u \in \{0, 1\}^3$$

which is satisfied if $H_1 \cdot G_2^T = H_1 \cdot H_1^T = 0$. This is indeed the case, as each row of H_1 has an even number of 1's.

Finally, C_1 corrects 1 error, because all pairs of columns of H_1 are independent and its third column is a linear combination of the first two, and therefore the minimal distance (between codewords) is $d = 3$ (and $t = 1$).

Moreover, $C_2^\perp = (C_1^\perp)^\perp = C_1$ corrects also 1 error.

- (b) The $\text{CSS}(C_2, C_1)$ code possesses parameters: $n = 7$ (length) $\dim \mathcal{H} = 2^7$ (\mathcal{H} subspace of Hilbert space of the 7 qubits).
 $k_1 - k_2 = \dim(C_1) - \dim(C_2) = 4 - 3 = 1$. The code $\text{CSS}(C_2, C_1)$ is a subspace of \mathcal{H} of dimension $2^1 = 2$. The code corrects $t = 1$ error.

(c) **Codewords:**

The equivalence class (or coset) of $c_0 = (0, 0, 0, 0, 0, 0, 0) \in C_1$ is:

$$\begin{aligned} |0\rangle_{\text{Steane}} &= \frac{1}{\sqrt{|C_2|}} \sum_{y \in C_2} |y\rangle \\ &= \frac{1}{\sqrt{8}} \left\{ |0000000\rangle + |1010101\rangle + |0110011\rangle + |0001111\rangle + \right. \\ &\quad \left. + |0111100\rangle + |1011010\rangle + |1100110\rangle + |1101001\rangle \right\}. \end{aligned}$$

where we used the list of 8 (classical) codewords of C_2 given in (??).

Besides, $c_1 = (1, 1, 1, 1, 1, 1, 1)$ is a codeword in C_1 which is not in C_2 (check!). Its equivalence class gives the other independent vector of Steane's code:

$$\begin{aligned} |1\rangle_{\text{Steane}} &= \frac{1}{\sqrt{|C_2|}} \sum_{y \in c_1 \oplus C_2} |y\rangle \\ &= \frac{1}{\sqrt{8}} \left\{ |1111111\rangle + |0101010\rangle + |1001100\rangle + |1110000\rangle + \right. \\ &\quad \left. + |100011\rangle + |0100101\rangle + |0011001\rangle + |0010110\rangle \right\}. \end{aligned}$$

A general codeword is a linear combination (by the superposition principle of quantum mechanics)

$$|\psi\rangle = \alpha |0\rangle_{\text{Steane}} + \beta |1\rangle_{\text{Steane}}$$

with $|\alpha|^2 + |\beta|^2 = 1$; $\alpha, \beta \in \mathbb{C}$. This code needs 7 qubits to correct an error (bit, phase, or bit-phase flip) on $t = 1$ qubit.